

Starlink Kit Gen 3 V4

Brand:

Product Code:

Availability:

Rp6.000.000



Description:

- STANDARD

- Antenna : Electronic Phased Array
- Field of View : 110°
- Orientation : Software Assisted Manual Orienting

• Weight :

2.9 kg (6.4 lb)

3.2 kg (7 (b) with Kickstand

3.8 kg (8.3 (b) with Kickstand & 15 m Cable

- Environmental Rating : IP67 Type 4
- Operating Temperature : -30°C to 50°C (-22°F to 122°F)
- Wind Speed : Operational: 96 kph+ (60 mph+)
- Snow Melt Capability : Up to 40 mm / hour (1.5 in / hour)
- Power Consumption : Average: 75 - 100 W

- ROUTER

- Product Dimensions : 43.4 x 298.6 x 120.4 mm (1.7 in x 11.76 in x 4.74 in)
- Wi-Fi Technology : 802.11 a/b/g/n/ac/ax
- Generation : WiFi 6
- Radio : Tri Band 4 x 4 MU-MIMO
- Ethernet Ports : Two (2) Latching Ethernet LAN ports with removable cover
- Coverage : Up to 297 m² (3,200 ft²)
- Operating Temperature : -30°C to 50°C (-22°F to 122°F)
- Weight : 0.57 kg (1.25 lbs)
- Security : WPA2
- Environmental Rating : IP56 Rated (Water Resistant), configured for indoor use
- Power Indicator : LED | face plate, lower left corner of router
- Mesh Compatibility : Compatible with Starlink Gen 2 and Gen 3 Mesh

Nodes, up to 3 Starlink Mesh Nodes (*Not compatible with 3 r d party m e s h s y s t e m s)

- Devices : Connect up to 235 devices

- POWER SUPPLY

- Product Dimensions : 173 × 93 × 35.75 mm (6.8 in x 3.66 in x 1.4 in)
- Weight : 0.65 kg (1.43 lbs)
- Environmental Rating : 1P66 Type 4
- Operating Temperature : -30°C to 60°C (-22 to 140°F)
- Power Specifications : 100-240V ~ 2.5A 50 - 60 Hz

• What's In The Box

1x STARLINK Standard Kit V4

1x Kickstand

1x Gen 3 Router

1x Starlink Cable 15M

1x AC Power Cable 1.5 m

1x Power Supply & Cable PS 1.5 m

- Package Weight : 6.73 kg (14.83 lbs)
- Package Dimensions : 652.4 x 451.7 × 97.9 mm (25.69 x 17.78 x 3.84 in)

